



FROZEN CARBONATED BEVERAGE DISPENSER MODEL: 561 Nitrogen Infused (60Hz)

SPECIFICATIONS

DIMENSIONS

DISPENSER

Width: 17 in (432mm)
Depth: 32.3 in (820mm)
Height: 35.9 in (912mm)

BASE CART (optional)

Width: 17 in (431 mm)
Depth: 34.1 in (866 mm)
Height: 34.5 in (876 mm)

WEIGHT

DISPENSER

Net Weight: 273 lbs (128.8 kg)
Shipping Weight: 305 lbs (138.3 kg)

BASE CART

Net Weight: 67 lbs (30.4 kg)
Shipping Weight: 115 lbs (52.2 kg)

SPACE REQUIREMENTS

Side and back: 2.0 in (51mm) minimum
Top: 12.0 in (305 mm) minimum

CAPACITY

Barrel Size 197 fl oz
Continuous draw: 3,600 fl oz/hr (base flavor, FCB)

REFRIGERATION

15,000 BTU/Hr, R-404A

MOTORS

Beater (1) 1/6 HP (120w)
Fan (1) 1/4 HP (135w)

SYRUP

(1) FCB Base Syrup
(4) Flavor Shot Concentrates
Bag-In-Box (BIB) Syrup and connections

WATER REQUIREMENTS

Fresh water, minimum 3/8" supply 30 psig (207 kPa) flowing

CO₂

Supply pressure: 70-72 psig (482.6 - 496.4 kPa)
Minimum 3/8" supply line

N₂ (NITROGEN must be food grade)

Supply pressure: 70-72 psig (482.6 - 496.4 kPa)
Minimum 3/8" supply line

ELECTRICAL REQUIREMENTS

215 to 245 VAC 60 Hz, single phase; 3 wire, 20 A circuit
L6-20R Receptacle required. Buck/boost transformer (optional)
required for operation outside this range.



- 10.1" Color Touchscreen
- Up to 16 different flavor combinations
- Tactile push button dispense
- Sold Out dispense lockout
- ADA compliant



NEMA L6-20R



The ICEE Company

A subsidiary of J&J Snack Foods Corp.

For more information please call: (800) 423-3872

Equipment design and/or specifications may change without notice. ICEE is a Federally Registered Trademark.

SS_561_B_IC_NITRO_SD_02-25-19