

FROZEN CARBONATED BEVERAGE DISPENSER MODEL 562

SPECIFICATIONS

DIMENSIONS

DISPENSER

Width: 17 in (432 mm) Depth: 32.3 in (820 mm)

Height: 41.4 in (1052 mm) to top of merchandiser

BASE CART (optional)

Width: 17 in (432 mm) Depth: 32.4 in (823 mm) Height: 34.5 in (876 mm)

WEIGHT

DISPENSER

Net Weight: 345 lbs (156.5 kg)

BASE CART

Net Weight: 67 lbs (30.4 kg)

41.4"

SPACE REQUIREMENTS

Side and back: 2.0 in (51mm) minimum Top: 12.0 in (305 mm) minimum

CAPACITY

Barrel Size 174 floz Continuous draw: 3,840 floz/hr (alternating barrels) Recovery Time 4 minutes

REFRIGERATION

14,900 BTU/Hr, R-404A (60Hz)

MOTORS

Beater (2) 1/6 HP (120w) Fan (1) 1/4 HP (135w)

SYRUP

Bag-In-Box (BIB) Syrup and connections

WATER REQUIREMENTS

Fresh water, minimum 3/8" supply 30 psig (207 kPa) flowing

CO,

Supply pressure: 70-72 psig (482.6 - 496.4 kPa) Minimum 3/8" supply line

ELECTRICAL REQUIREMENTS

200 to 245 VAC 60 Hz, single phase; 3 wire, 20 A circuit L6-20R Receptacle required.





FEATURES AND BENEFITS

- The Highest Capacity and Quality in the Industry
- Programmable Defrost
- User Friendly System Controls on Large LCD Screen
- LED Lighted Merchandiser and Flavor Cards
- · Individual Flavor Barrel adjustability



34"