

SPECIFICATIONS

DIMENSIONS

DISPENSER Width: 20.3 in (516 mm) Depth: 32.3 in (820 mm) Height: 41.4 in (1052 mm) to top of merchandiser

41.4"

BASE CART (optional) Width: 20.3 in (516 mm) Depth: 32.4 in (822 mm) Height: 34.5 in (876 mm)

WEIGHT DISPENSER Net Weight: 390 lbs (177 kg)

BASE CART Net Weight: 74 lbs (33.6 kg)

SPACE REQUIREMENTS Side and back: 2.0 in (51mm) minimum Top: 12.0 in (305 mm) minimum

CAPACITY

Barrel Size 174 floz Continuous draw: 3,840 floz/hr (alternating barrels) Recovery time 4 minutes

REFRIGERATION 14,900 BTU/Hr, R-404A (60Hz)

MOTORS Beater (3) 1/6 HP (120w) Fan (1) 1/4 HP (135w)

SYRUP Bag-In-Box (BIB) Syrup and connections

WATER REQUIREMENTS Fresh water, minimum 3/8" supply

30 psig (207 kPa) flowing

CO₂ Supply pressure: 70-72 psig (482.6 - 496.4 kPa) Minimum 3/8" supply line

ELECTRICAL REQUIREMENTS

200 to 245 VAC 60 Hz, single phase; 3 wire, 20 A circuit L6-20R Receptacle required.



NEMA L6-20R



FEATURES AND BENEFITS

- The Highest Capacity and Quality in the Industry
- Programmable Defrost
- User Friendly System Controls on Large LCD Screen
- LED Lighted Merchandiser and Flavor Cards
- Individual Flavor Barrel adjustability