



# FROZEN CARBONATED BEVERAGE DISPENSER MODEL: 772 MIU (60Hz)

## SPECIFICATIONS

### AIR COOLED DIMENSIONS

#### DISPENSER

Width: 17" (432 mm)  
Depth: 32.5" (826 mm)  
Height: 34.0" (864 mm)

#### WEIGHT

Operating: 333 lbs (151 kg)  
Empty: 310 lbs (141 kg)

### CLEARANCE REQUIREMENTS

Sides or Back: 3 in. (76 mm) Minimum  
Top: **12-36 inches:** 12 in. (304 mm) Minimum with Side or Back Open-Air Conditions, 36 in. (914 mm) Minimum in Equipment Alcove.

### CAPACITY

Barrel Volume: **176oz** (5205 ml)  
4500 oz/hr. 133,081 ml/hr) continuous, alternating barrels  
Recover time: 4 Minutes

### REFRIGERATION

15,000 BTU/Hr. (15,826 kJ/hr) R-404A (60Hz)

### SYRUP

(2) FCB Base Syrup  
(8) Flavor Injection Syrup  
Bag-In-Box (BIB) syrup and connections

### MOTORS

Beater: (2) 1/6 HP (120 w)  
Fan: 1/4 HP (135 w)

### WATER REQUIREMENTS

Fresh water, minimum 3/8" supply, 30 psi flowing (207 kPa)  
Water Flow Rate: 1.5 oz/sec from Solution Module

### CO<sub>2</sub>

Supply pressure: 70-72 psig (483 - 496 kPa)

### ELECTRICAL REQUIREMENTS

208 to 254 VAC single phase; 3 wire, 20 amp;  
uses NEMA #L-620R receptacle (60 Hz)  
Buck-boost transformer required for operation outside this range



### GRAPHICS

DURATRANS: 6 1/2 in x 15 3/4 in (165 mm x 400 mm)

#### Digital

Touch Screen 13.3 inch (338 mm) (uses same digital graphics as 561)

