



# FROZEN CARBONATED BEVERAGE DISPENSER MODEL: 774 (60Hz)

## SPECIFICATIONS

### AIR COOLED

### DIMENSIONS

#### DISPENSER

Width: 26" (660 mm)  
Depth: 32.5" (826 mm)  
Height: 41.4" (1052 mm)

#### WEIGHT

Empty: 418 lbs (190 kg)  
Operating: 464 lbs (211 kg)

#### CLEARANCE REQUIREMENTS

Sides or Back: 3 in. (76 mm) Minimum  
Top: 12 in. (304 mm) Minimum with Side or Back Open-Air Conditions  
36 in. (914 mm) Minimum in Equipment Alcove

#### CAPACITY

Barrel Volume: 176 oz  
Continuous Draw (alternating barrels): 5,160 oz/hour  
Recovery Time (75°F ambient): 4 Minutes

#### REFRIGERATION

19,000 BTU/Hr, R-404A (60 Hz)

#### SYRUP

(4) FCB Base Syrup Flavors  
Bag-In-Box (BIB) syrup and connections

#### MOTORS

Beater: (4) 1/6 HP (120 w)  
Fan: 1/4 HP (135 w)

#### WATER REQUIREMENTS

Fresh Water, Minimum 3/8" Supply, 30 psi Flowing (207 kPa) Water Flow Rate: 1.5 oz/sec from Solution Module

#### CO<sub>2</sub>

Supply pressure: 70-72 psig (482.6 - 496.4 kPa)

#### ELECTRICAL REQUIREMENTS

208-254 VAC Single Phase, 3 Wire, 30 Amp  
Uses NEMA #L-630R Receptacle (60 Hz)  
buck-boost transformer required for operation outside this range.

#### GRAPHICS

Duratrans: 17 3/4 in x 25 7/8 in (451 mm x 657 mm)  
Flavor Card: 4 7/8 in x 3 1/2 in (124 mm x 89 mm)

